



Bar Cutting Machines



Type	R.P.M	Motor	45 kg/mm ²			65 kg/mm ²			80 kg/mm ²			Dimensions	Weight
			1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø		
C30 TF	107	3				26	18	14	22	16	12	80 x 57 x h 75 cm	250 kg
C30 MF	107	2,5-1,8				26	18	14	22	16	12	80 x 57 x h 75 cm	250 kg
C36 TF	65	4				30	22	18	28	20	16	100 x 70 x h 84 cm	390 kg
C42	90	4	42	34	26	36	28	22	34	26	20	118 x 71 x h 87 cm	660 kg
C52	40	5,5	52	40	30	44	32	24	40	30	22	130 x 71 x h 92 cm	730 kg
C55	40	5,5	55	42	32	46	34	26	42	28	22	130 x 91 x h 92 cm	750 kg
C70	38	7,5	70	50	40	60	42	30	52	34	26	162 x 81 x h 109 cm	950 kg



Bar Bender Machines



Standard Equipment

Pins, bushes, checking block and foot remote control are supplied as standard tools on any machines according to their sizes.



Type	R.P.M	Motor	45 kg/mm ²			65 kg/mm ²			80 kg/mm ²			Dimensions	Weight
			1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø		
P26	13	2	26	20	16	24	18	14	22	14	12	75 x 76 x h 84 cm	250 kg
P30	10	2	30	24	18	26	20	16	24	18	14	81 x 81 x h 85 cm	310 kg
P32	9	3	32	26	20	28	22	18	26	20	16	84 x 83 x h 85 cm	350 kg
P36	9	4	6	26	22	32	24	18	30	22	16	86 x 85 x h 85 cm	400 kg
P42	6	4	42	30	26	36	28	24	34	26	22	90 x 86 x h 89 cm	600 kg
P52	6	5,5	52	36	30	46	34	26	42	32	24	95 x 91 x h 89 cm	640 kg
P55	5	5,5	55	32	28	48	36	24	44	34	26	140 x 95 x h 93 cm	770 kg



Combined Machines



Type	R.P.M.	Motor	45 kg/mm ²			65 kg/mm ²			80 kg/mm ²			Dimensions	Weight
			1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø		
TP 26 32	9	3	26	20	14	24	18	12	22	16	10	85 x 101 x h 85 cm	440 kg
			32	26	20	28	22	18	26	20	16		
TP 30 35	9	4	30	22	18	26	20	16	22	18	14	85 x 110 x h 85 cm	450 kg
			35	26	22	30	24	18	28	22	16		
TP 38 45	6	5,5	38	26	22	34	24	20	32	22	18	104 x 116 x h 89 cm	790 kg
			45	30	26	40	28	24	36	26	22		

Security rules



Anti-repeating
system



Cover-blade
protection grating



Magneto thermic
switch



Stop system cover-blade
for combined machines