

## CISAILLE



Type	R.P.M	Motor	45 kg/mm <sup>2</sup>			65 kg/mm <sup>2</sup>			80 kg/mm <sup>2</sup>			Dimensions	Weight
			1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø		
<b>C30 TF</b>	107	3				26	18	14	22	16	12	80 x 57 x h 75 cm	250 kg
<b>C30 MF</b>	107	2,5-1,8				26	18	14	22	16	12	80 x 57 x h 75 cm	250 kg
<b>C36 TF</b>	65	4				30	22	18	28	20	16	100 x 70 x h 84 cm	390 kg
<b>C42</b>	90	4	42	34	26	36	28	22	34	26	20	118 x 71 x h 87 cm	660 kg
<b>C52</b>	40	5,5	52	40	30	44	32	24	40	30	22	130 x 71 x h 92 cm	730 kg
<b>C55</b>	40	5,5	55	42	32	46	34	26	42	28	22	130 x 91 x h 92 cm	750 kg
<b>C70</b>	38	7,5	70	50	40	60	42	30	52	34	26	162 x 81 x h 109 cm	950 kg

## CINTREUSE



### Standard Equipment

Pins, bushes, checking block and foot remote control are supplied as standard tools on any machines according to their sizes.



Type	R.P.M	Motor	45 kg/mm <sup>2</sup>			65 kg/mm <sup>2</sup>			80 kg/mm <sup>2</sup>			Dimensions	Weight
			1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø		
<b>P26</b>	13	2	26	20	16	24	18	14	22	14	12	75 x 76 x h 84 cm	250 kg
<b>P30</b>	10	2	30	24	18	26	20	16	24	18	14	81 x 81 x h 85 cm	310 kg
<b>P32</b>	9	3	32	26	20	28	22	18	26	20	16	84 x 83 x h 85 cm	350 kg
<b>P36</b>	9	4	6	26	22	32	24	18	30	22	16	86 x 85 x h 85 cm	400 kg
<b>P42</b>	6	4	42	30	26	36	28	24	34	26	22	90 x 86 x h 89 cm	600 kg
<b>P52</b>	6	5,5	52	36	30	46	34	26	42	32	24	95 x 91 x h 89 cm	640 kg
<b>P55</b>	5	5,5	55	32	28	48	36	24	44	34	26	140 x 95 x h 93 cm	770 kg

## FICHE TECHNIQUE COMBINEE



Type	R.P.M.	Motor	45 kg/mm <sup>2</sup>			65 kg/mm <sup>2</sup>			80 kg/mm <sup>2</sup>			Dimensions	Weight
			1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø	1 Ø	2 Ø	3 Ø		
TP 26 32	9	3	26	20	14	24	18	12	22	16	10	85 x 101 x h 85 cm	440 kg
			32	26	20	28	22	18	26	20	16		
TP 30 35	9	4	30	22	18	26	20	16	22	18	14	85 x 110 x h 85 cm	450 kg
			35	26	22	30	24	18	28	22	16		
TP 38 45	6	5,5	38	26	22	34	24	20	32	22	18	104 x 116 x h 89 cm	790 kg
			45	30	26	40	28	24	36	26	22		